



ST 3.60 C5

PORTABLE POWER

WATERPUMP Range AQUALINE INTENS

PRODUCT ADVANTAGES

- HONDA Professional Engine
- · Automatic priming
- Offeres accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE INTENS

Designed for water with low solid content.















ST 3.60 C5

WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Clear water with little sediment pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	900
Outlflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3,10
75% cons. (I/h) *	0,90
75% Autonomy (h) *	3,40
Sound power level guaranteed LwA dB(A)	105
Acoustic pressure level @1m in dB(A)	90
Acoustic pressure level @7m in dB(A)	75

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Distribution	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (I)	0,60

DIMENSIONS AND WEIGHT

Length (cm)	50,50
Width (cm)	41,40
Height (cm)	44,80
Dry Weight (kg)	29

PACKAGING

Packaging type	Box	
Length (cm)	52	
Width (cm)	42,50	
Height (cm)	46,50	
Weight (kg)	32	
Pallet type	120/80	
Number of box by pallet	12	
Pallet height (cm)	153	
weight of the packaged Pallet (kg)	394	





ST 3.60 C5

ACCESSORIES SUPPLIED



Inlet filter

RBH0-5

R12

R14

Screw-on connectors



Circlips

User and maintenance manual



RBH1 Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RHO Cover for SDMO 's generating sets, welding sets and water pumps



Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.



Rapid connections kit for 3 water pumps.

