



## XT 3.78 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

### PRODUCT ADVANTAGES

- HONDA Professional Engine
- Easy acces to the turbine (without tools)
- Automatic priming
- Resistant pump-barrel
- Offeres accessories

### Range AQUALINE SPECIALIST

High performance under extreme conditions.



## XT 3.78 C5

### WATER PUMP SPECIFICATIONS

|  |   |
|--|---|
| Range                                  | AQUALINE SPECIALIST                     |
| Type liquid                            | Extremely heavily sedimented water pump |
| Suction diameter [mm]                  | 76                                      |
| Backflow diameter (mm)                 | 76                                      |
| Outflow maximum (L/min)                | 1340                                    |
| Outflow maximum (m3/h)                 | 80,40                                   |
| Lifting height (m)                     | 27                                      |
| Suction height (m)                     | 8                                       |
| Granulometry (mm)                      | 27                                      |
| Automatic priming                      | Yes                                     |
| Fuel                                   | Petrol                                  |
| Tank (L)                               | 5,30                                    |
| 75% cons. (l/h) *                      | 2                                       |
| 75% Autonomy (h) *                     | 2,70                                    |
| Sound power level guaranteed LwA dB(A) | 110                                     |
| Acoustic pressure level @1m in dB(A)   | 94                                      |
| Acoustic pressure level @7m in dB(A)   | 80                                      |

### ENGINE SPECIFICATIONS

|   |          |
|---|----------|
| Engine brand                              | HONDA    |
| Engine ref.                               | GX240_C5 |
| Distribution                              | O.H.V.   |
| Start                                     | Starter  |
| Oil shutdown                              | Oui      |
| Displacement (cm3)                        | 242      |
| Oil system capacity including filters (l) | 1,10     |

### DIMENSIONS AND WEIGHT

|                 |       |
|-----------------|-------|
| Length (cm)     | 69    |
| Width (cm)      | 48,50 |
| Height (cm)     | 53,20 |
| Dry Weight (kg) | 58    |

### PACKAGING

|                                    |        |
|------------------------------------|--------|
| Packaging type                     | Box    |
| Length (cm)                        | 72     |
| Width (cm)                         | 52     |
| Height (cm)                        | 58     |
| Weight (kg)                        | 68,50  |
| Pallet type                        | 120/80 |
| Number of box by pallet            | 4      |
| Pallet height (cm)                 | 129    |
| weight of the packaged Pallet (kg) | 284    |

# KOHLER®

# SDMO®

## XT 3.78 C5

### ACCESSORIES SUPPLIED



Inlet filter

Screw-on connectors



Circlips

User and maintenance manual



### OPTIONS



**RHO** Cover for SDMO 's generating sets, welding sets and water pumps



**R12** Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.



**R14** Rapid connections kit for 3 water pumps.